

Technical Specifications - Overland Series by Pastorelli

| Specification | Standard | EN 14411 Standard | Pastorelli Results |
|--|--------------|--------------------------|-----------------------|
| Water Absorption | ISO 10545-3 | ≤ 0.5% | 0.1% |
| Bending Strength | ISO 10545-4 | ≥ 35 N/mm ² | 45 N/mm ² |
| Resistance to Deep Abrasion | ISO 10545-6 | Max. 175 mm ³ | < 150 mm ³ |
| Linear Thermal Expansion | ISO 10545-8 | ≤ 9 MK ⁻¹ | ≤ 9 MK ⁻¹ |
| Thermal Shock Resistance | ISO 10545-9 | Required | Resists |
| Frost Resistance | ISO 10545-12 | Required | Resists |
| Resistance to Acids & Bases | ISO 10545-13 | Required | Resists |
| Resistance to Cleaning Products & Pool Reactives | ISO 10545-13 | Minimum UB | Minimum UB |
| Resistance to Stains | ISO 10545-14 | ≥ 3 | ≥ 4 |
| Slip Resistance | DIN 51130 R | - | R9 |

| Available Sizes (inches) & Finishes | Natural |
|-------------------------------------|---------|
| 6x6 | x |
| 12x12 | x |
| 18x18 | x |
| 2x2 Mosaic | x |
| 3x6 Brick Mosaic | x |